coverguard®

TECHNICAL DATASHEET

EUROCUT P600

Ref.

1CUPF00

Cut - Precision Work









Dry Environment













The +

Highest level of cut protection: CUT F Dexterity Crotch between thumb and index Touchscreen

Heat protection 100°C / 15 sec. Dirt resistant

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
1CUPF00007	7	10	100
1CUPF00008	8	10	100
1CUPF00009	9	10	100
1CUPF00010	10	10	100
1CUPF00011	11	10	100

SALES PACKAGING

Hangable individual polybag

DESCRIPTION

Grey seamless support from HDPE,

Black PU palm coating,

Nitrile crotch reinforcement between thumb and index,

Knitted wrist

Certified OEKO-TEX® STANDARD 100, CQ 1301/1, IFTH

SECTORS

Light Industries

Maintenance

Services and distribution

APPLICATIONS

Handling in dry area with mechanical and thermal risks, for glass industry, automotive or aeronautical industries, injection moulding, construction, logistics,...

TECHNICAL FEATURES

Gauge 13

Color Grey Color 2 Black Shape Glove

Gloves environment Dry environment Glove type Seamless knitting

Support material HDPE polyester Elastane

Coating level Palm ΡU Material of coating Coating finition Smooth

Reinforced part place Between thumb and index

finger

Reinforced part material Nitrile Type Of Cuff Elastic wrist

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/162/05/20/1556

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France

EPI CAT. II

EN420:2003 + A1:2009

General requirements for protective gloves

EN388:2016



4.X.4.4.F.

Protection from mechanical risks

ANSI



EN407:2004

Cut resistance ANSI/SEA 105-2016 / ASTM F2992M-15



Protection from heat and fire

RETAILER STAMP

MAJ 10/07/2023