

Ref. 6GOE300

Non Vented Helmet General Use



356g

The +

Lightweight
Dielectric 440V a.c.
UV resistant
Thermic resistance: +50 -20 °C
"Sponge and fabric" front sweatband

Front surface suitable for badge holder
Fits with earcups 60750 / 60755 / 60757/ 6MX3000NSI

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
6GOE300NSI	-		24

SALES PACKAGING



Individual polybag

See also

VARIANTS



DESCRIPTION

High density polyethylene shell
6 points polyethylene suspension harness
Not vented
Manual adjustment from 53 to 62cm, 2mm increments
27cm fabrics sweatband
UV resistant
Front surface suitable for badge holder (6POBA00NSI)
Fits with earcups 60750 / 60755 / 60757
Suitable with Hi-Viz stickers 6STI000NSI

SECTORS

Heavy & process industries
Light Industries
Regional/public authorities
Infrastructure, building industry

APPLICATIONS

Construction site, building and public works, industry...

TECHNICAL FEATURES

Shape	Safety helmet	Other features	Electrical insulation EBT 440 Va
Weight	356g		Thermic Résistance : +50/-20°C
Color	Red		Lightweight = 356g
Features	HDPE shell high density polyethylene		Use by date : 60 month
	6 suspension point harness		Delivered assembled
	Size adjustment by slide from 53 to 62 cm		
	Electrical insulation EBT 440 va		

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate **DPI/0497/698**

Delivered by CSI (0497) Cascina Traversagna- 21 20030 Senago (MI) Italy



EPI CAT. II

EN397:2012 + A1:2012

Industrial safety helmets

RETAILER STAMP

MAJ 26/05/2023