

Half Mask



The +

Strength, stability and resistance
Ergonomic shape: lightweight and adaptability on any face shape providing extreme comfort
4 point support head harness with plastic harness
2 filters for a good balance
Exhalation valve: reduction of breathing resistance and avoid fog and heat inside the mask
Innovative production method

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
6ETN200NSI	-		16

SALES PACKAGING

Hangable individual box

DESCRIPTION

Half-mask in TPE and polypropylene self-extinguishing - used with 2 filters (not included), soft silicone exhalation valve, fabric and rubber elastic strap

SECTORS

Heavy & process industries
Light Industries
Infrastructure, building industry
Transport (excluding manufacturing) and logistics

APPLICATIONS

For regular and prolonged use in a dangerous environment: industrial maintenance, fertilizer spreading, chemical industry, paint application, carpentry, wood industry, cement industry, metal cutting...

TECHNICAL FEATURES

Shape	Half Mask	Features	Half masks 2 filters (non included)
Weight	130g		Innovative production method : master combination of self-extinguishing TPE rubber and polypropylen.
Harness	Harness made of plastic		Inner part designed with Cad-Cam technology
features			
Main risk	Respiratory protection from aerosols and gases and vapours	Other features	Used with 2 filters (not included). Soft silicone exhalation valve, 2 inhalation valves positioned under the filters. Fabric elastic straps with 4 points and head harness. Use exclusively with: 6REF330NSI, 6REF340NSI, 6REF350NSI, 6REF360NSI, 6REF370NSI.
Color	Light grey		
Color 3	Lime		

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate PPE060AT1982

Delivered by ITALCERT (0426) Viale Sarca- 336 20126 - MILANO Italy



EPI CAT. III

EN140:1998

Half masks and quarter masks