

Ref. 6GOE800

Non Vented Helmet General Use



356g

0%  
METAL

The +

Lightweight  
Dielectric 440V a.c.  
UV resistant  
Thermic resistance: +50 -20 °C  
"Sponge and fabric" front sweatband  
Adjustable from 53 to 62cm (2mm increments)

Front surface suitable for badge holder  
Fits with earcups 60750 / 60755 / 60757 / 6MX3000NSI

### DESCRIPTION

High density polyethylene shell  
6 points polyethylene suspension harness  
Not vented  
Manual adjustment from 53 to 62cm, 2mm increments  
27cm fabrics sweatband  
UV resistant  
Front surface suitable for badge holder (6POBA00NSI)  
Fits with earcups 60750 / 60755 / 60757 / 6MX3000NSI  
Suitable with Hi-Viz stickers 6STI000NSI

### SECTORS

Heavy & process industries

Light Industries

Regional/public authorities

Infrastructure, building industry

### APPLICATIONS

Construction site, building and public works, industry...

### PURCHASE PACKAGING

Ref.	Size	Inner	Carton
6GOE800NSI	-		24

### SALES PACKAGING

x1

Individual polybag

See also

### VARIANTS



## TECHNICAL FEATURES

Shape Safety helmet  
Weight 356g  
Color Green

**Features** HDPE shell high density polyethylene  
6 suspension point harness  
Size adjustment by slide from 53 to 62 cm  
(2mm increment)  
Electrical insulation EBT 440 va

**Other features** Electrical insulation EBT 440 Va  
Thermic Résistance : +50/-20°C  
Lightweight = 356g  
Use by date : 60 month  
Delivered assembled

## STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate **DPI/0497/698**

Delivered by CSI (0497) Cascina Traversagna- 21 20030 Senago (MI) Italy

EPI CAT. II

EN397:2012 + A1:2012

Industrial safety helmets

RETAILER STAMP

MAJ 11/07/2023