## coverguard®

# TECHNICAL DATASHEET MERCURIO 4

Ref. 6MER400

#### Welding



### The +

Large viewing area: 100 x 41mm
Auto-darkening shade from 9 to 13
Automatic adjustment of the shade in
0,4ms, back to clear in 0,1 to 1,0ms
Power supplied by batteries and solar cell
Ratchet adjustable headband

Compatible with prescription glasses, breathing masks...

#### PURCHASE PACKAGING

**Ref. Size Inner Carton** 6MER400NSI - 17

#### SALES PACKAGING

x1

Individual pack

See also

#### **VARIANTS**



6MER200

#### **DESCRIPTION**

Welding helmet MERCURIO 4. Made in Europe, 4 light detectors Low amperage TIG rated 5A, Internal shade control, ratchet adjustable headguard, Field of vision: 100x41mm, power supplied by solar cell and battery, made of polyamide/nylon

#### **SECTORS**

Heavy & process industries (steel, metallurgy, paper, concrete, plaster...)

DIY

Services and distribution

#### **APPLICATIONS**

Electronic welding, MIG, MIC, MAG/CO2, Air, arc gouging, TIG, PLASMA jet cutting

#### TECHNICAL FEATURES

Color Black

**Features** Solar cell response time of: 0.4ms

4 light detectors

Low amperage TIG rated 5A

Adjustable shade and return from dark to clear

thanks to internal knob

Comfortable head gear, adjustable by ratchet

Field of vision: 100x41mm

Power supplied by solar cell and battery

Weight 528g
Frame Nylon
Lens colour 9 to 13
Shade 9 to 13
Dimensions 100x41mm
Main risk Eye protection

#### STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate **C1766.3PCX**Delivered by ECS (1883) Hüttfeldstraße 50 73430 Aalen Germany

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate **C1766.3PCX** Delivered by ECS (1883) Hüttfeldstraße 50 73430 Aalen Germany

 $\epsilon$ 

EPI CAT. II

EN175:1997

Welding equipments

EN379:2003+A1:2009

Welding filters with variable shade or dual shade

RETAILER STAMP

MAJ 03/09/2021