

Ref. 6PHP160

Non Vented Helmet General Use



The +

PERFORMANCE : High resistance level (lateral deformation(LD), molten metal splashes(MM), low temperature -30°C) // ABS Shell // CLASS 0: electrical insulation for use on low voltage installations up to 1000V a.c and 1500V d.c

COMFORT : Integrated safety glasses // Good fitting and lightweight feeling (head balance, 450g) // Easy adjustment by ratchet // Wide field of vision thanks to the short peak // 3D textile sweatband

CUSTOMIZATION : Add your logo (optionnal, on demand) Compatible with badge holder (6POBA) and earmuffs (6MX3000NSI)

DESCRIPTION

PHOENIX PRO safety helmet. ABS shell, 6 points suspension harness in polyethylene with 6 textile webbing, size adjustment by ratchet from 52 to 63cm, short peak, integrated safety glasses with anti-scratch K standard and anti-fog N standard, side euro slot adapters, 3D textile sweatband, 4 points chinstrap as a standard

SECTORS

- Heavy & process industries
- Mechanicals constructions
- Light Industries
- Regional/public authorities
- Infrastructure, building industry

APPLICATIONS

Construction site, building and public works, industry...

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
6PHP160NSI	-	-	16

SALES PACKAGING



Individual polybag

See also

VARIANTS



6PHP200



6PHP400



TECHNICAL FEATURES

Shape	Safety helmet	Main risk	Prevention from falling objects and head injuries or head trauma
Weight	450g	Value electric isolation	1000V a.c / 1500V d.c
Lens marking	3-1.2 1 B	Shell material	ABS
Shade	Clear	Color	HV Yellow
Harness features	6 points harness made of polyethelene 6 textile webbings	Color 2	Black
		Features	ABS Shell LDPE 6 points harness Size adjustment from 52 to 63 cm Class 0: electrical insulation up to 1000V a.c and 1500V d.c
		Service life	Manufacturing date indicated under the peak Use for 10 years in good conditions
		Adjustment	Adjustment by ratchet from 52 to 63 cm

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate DPI/0497/2313

Delivered by CSI (0497) Cascina Traversagna- 21 20030 Senago (MI) Italy



EPI CAT. III

EN166:2001

Specifications (optical quality, resistance to usual risks, mechanical risks, resistance to impacts)

EN397:2012 + A1:2012

Industrial safety helmets

EN50365:2002

Electrically insulating helmets for use on low voltage installations (used for working on or near live parts of installations not exceeding 1,000 V AC or 1,500 V DC)

COVERPERF - Skincare



Dermatological safety approved after direct contact with the skin for 48 hours. No irritation was observed at the end of the test.