

TECHNICAL DATASHEET PHOENIX WIND

6PHW160 Ref.

Vented Helmet General Use



DESCRIPTION

PHOENIX WIND Safety helmet. ABS shell, 6 points suspension harness in polyethylene with 6 textile webbing, size adjustment by ratchet from 52 to 63cm, side ventings, short peak, integrated safety glasses with antiscratch K standard and anti-fog N standard, side euro slot adapters, 3D textile sweatband, 4 points chinstrap as a standard

SECTORS

Heavy & process industries

Mechanicals constructions

Light Industries

Regional/public authorities

Infrastructure, building industry

APPLICATIONS

Construction site, building and public works, industry...



The +

PERFORMANCE : High resistance level (lateral deformation(LD), molten metal splashes(MM), low temperature -30°C) // ABS Shell

COMFORT : Integrated safety glasses // Good fitting and lightweight feeling (head balance, 450g) // Easy adjustment by ratchet // Wide field of vision thanks to the short peak // 3D textile sweatband CUSTOMIZATION : Add your logo (optionnal, on demand) Compatible with badge holder (6POBA) and earcups (6MX3000NSI)

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
6PHW160NSI	-		16

SALES PACKAGING



Individual polybag

See also



6PHW200

6PHW170

6PHW800

COVERGUARD

coverguard

PHOENIX WIND

TECHNICAL FEATURES

Shape	Safety helmet	Color	HV Yellow
Weight	450g	Color 2	Black
Shade	Clear	Features	ABS Shell
Harness	6 points harness made of polyethelene		LDPE 6 points harness
features	6 textile webbings		Size adjustment from 52 to 63 cm
Main risk	Prevention from falling objects and head injuries or head trauma	Service life	Manufacturing date indicated under the peak
Shell material	ABS		Shelf life: Storage for 2 years in standard conditions
			Use for 5 years in good conditions
		Adjustmen-t	Adjustment by ratchet from 52 to 63 cm

Vented

Side ventings

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate DPI/0497/2314

Delivered by CSI (0497) Cascina Traversagna- 21 20030 Senago (MI) Italy

CE	EPI CAT. II
EN166:2001	Specifications (optical quality, resistance to usual risks, mechanical risks, resistance to impacts)
EN397:2012 + A1:2012	Industrial safety helmets
COVERPERF - Skincare	

Dermatological safety approved after direct contact with the skin for 48 hours. No irritation was observed at the end of the test.

MAJ 22/10/2024