

## **TECHNICAL DATASHEET**

# PHOENIX PRO

Ref. 6PHP160

### Non Vented Helmet General Use

















## The +

PERFORMANCE: High resistance level (lateral deformation(LD), molten metal splashes(MM), low temperature -30°C) // ABS Shell // CLASS 0: electrical insulation for use on low voltage installations up to 1000V a.c and 1500V d.c

COMFORT: Integrated safety glasses // Good fitting and lightweight feeling (head balance, 450g) // Easy adjustment by ratchet // Wide field of vision thanks to the short peak // 3D textile sweatband CUSTOMIZATION: Add your logo

(optionnal, on demand)
Compatible with badge holder
(6DORA) and carrying (6MY2000NS)

(6POBA) and earcups (6MX3000NSI)

#### **DESCRIPTION**

PHOENIX PRO safety helmet. ABS shell, 6 points suspension harness in polyethylene with 6 textile webbing, size adjustment by ratchet from 52 to 63cm, short peak, integrated safety glasses with anti-scratch K standard and anti-fog N standard, side euro slot adapters, 3D textile sweatband, 4 points chinstrap as a standard

#### SECTORS

Heavy & process industries

Mechanicals constructions

**Light Industries** 

Regional/public authorities

Infrastructure, building industry

#### APPLICATIONS

Construction site, building and public works, industry...

#### **PURCHASE PACKAGING**

Ref. Size Inner Carton 6PHP160NSI - 16

#### SALES PACKAGING



Individual polybag

See also

#### **VARIANTS**







6PHP200

6PHP400

6PHP170

Main risk

#### TECHNICAL FEATURES

Shape Safety helmet Value electric 1000V a.c / 1500V d.c

isolation Weight 450g Lens marking 3-1.21B Shell material **ABS** Shade Clear Color **HV Yellow** Harness 6 points harness made of polyethelene Color 2 Black features 6 textile webbings **Features ABS Shell** 

Prevention from falling objects and head

injuries or head trauma

LDPE 6 points harness

Size adjustment from 52 to 63 cm

Class 0: electrical insulation up to 1000V

a.c and 1500V d.c

Service life Manufacturing date indicated under the

peak

Use for 10 years in good conditions

Adjustment Adjustment by ratchet from 52 to 63 cm

### STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate DPI/0497/2313

Delivered by CSI (0497) Cascina Traversagna- 21 20030 Senago (MI) Italy

EPI CAT. III  $\epsilon$ 

EN397:2012 + A1:2012 Industrial safety helmets

EN50365:2002 Electrically insulating helmets for use on low voltage installations (used for working on or near live parts of installations not exceeding 1,000 V AC or 1,500 V DC)

Dermatological safety approved after direct contact with the skin for 48 hours. No irritation was observed at the end of the test.