

TECHNICAL DATASHEET

PHOENIX PRO

6PHP200 Ref.

Non Vented Helmet General Use





DESCRIPTION

PHOENIX PRO Safety helmet. ABS shell, 6 points suspension harness in polyethylene with 6 textile webbing, size adjustment by ratchet from 52 to 63cm, short peak, integrated safety glasses with anti-scratch K standard and anti-fog N standard, side euro slot adapters, 3D textile sweatband, 4 point chinstrap as a standard

SECTORS

Heavy & process industries

Mechanicals constructions

Light Industries

Regional/public authorities

Infrastructure, building industry

APPLICATIONS

Construction site, building and public works, industry...











PERFORMANCE: High resistance level (lateral deformation(LD), molten metal splashes(MM), low temperature -30°C) // ABS Shell // CLASS 0: electrical insulation for use on low voltage installations up to 1000V a.c and 1500V d.c

COMFORT: Integrated safety glasses // Good fitting and lightweight feeling (head balance, 450g) // Easy adjustment by ratchet // Wide field of vision thanks to the short peak // 3D textile sweatband

(optionnal, on demand) Compatible with badge holder

CUSTOMIZATION: Add your logo

(6POBA) and earcups (6MX3000NSI)

PURCHASE PACKAGING

Ref. Size Inner Carton 6PHP200NSI 16

SALES PACKAGING



Individual polybag

See also

VARIANTS







TECHNICAL FEATURES

Shape Safety helmet Value electric 1000V a.c / 1500V d.c

Weight450gisolationLens marking3-1.21BShell materialABSShadeClearColorBlueHarness6 points harness made of polyetheleneColor 2Black

Harness6 points harness made of polyetheleneColor 2Blackfeatures6 textile webbingsFeaturesABS Shell

Main risk Prevention from falling objects and head LDPE 6 points harness

injuries or head trauma

Size adjustment from 52 to 63 cm

Class 0: electrical insulation up 1000V a.c

Service life Manufacturing date indicated under the

and 1500V d.c

peak Use for 10 years in good conditions

Adjustment Adjustment by ratchet from 52 to 63 cm

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate DPI/0497/2313

Delivered by CSI (0497) Cascina Traversagna- 21 20030 Senago (MI) Italy

 ϵ

EPI CAT. III

EN166:2001 Specifications (optical quality, resistance to usual risks, mechanical risks, resistance

to impacts)

EN397:2012 + A1:2012 Industrial safety helmets

EN50365:2002 Electrically insulating helmets for use on low voltage installations (used for working

on or near live parts of installations not exceeding 1,000 V AC or 1,500 V DC)

COVERPERF - Skincare



Dermatological safety approved after direct contact with the skin for 48 hours. No irritation was observed at the end of the test.

MAJ 03/06/2024