

Ref. 6REF410

Cartridges Eurmask

Breathing resistance :
* 15 l/min : 0,75 mbar.
* 47,5 l/min : 3,3 mbar.

The +

SUITABLE WITH NEW EURMASK 22102

PURCHASE PACKAGING

| Référence | Taille | Sachet | Carton |
|------------|--------|--------|--------|
| 6REF410NSI | | | 16 |



* Combined filter with special threaded connection for A2 organic gases and vapours with boiling point above 65°C.

* Must be used only by pair with NEW EURMASK 22102 (#7400)

* Body of the cartridge in HDPE

* Filtering material : active carbon and filtering non-woven PP.

SECTORS

Farming, silviculture and fishing

Heavy & process industries

Light Industries

Infrastructure, building industry

APPLICATIONS

Organic gas and vapours with boiling point > 65°C

For regular and prolonged use in a dangerous environment: industrial maintenance, Fertilizer spreading, chemical industry, paint application, ...

Do not use in a place where oxygen concentration is less than 17 vol. %

TECHNICAL FEATURES

| | |
|-----------------------|--|
| Features | A2 |
| Other features | Filtering material : active carbon and filtering non-woven PP. |
| Weight | 80 g |
| Specifications | Breathing resistance : * 15 l/min : 0,75 mbar. * 47,5 l/min : 3,3 mbar. * Class 2 according to EN14387:2004 |

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate **PPE060AT1587**

Delivered by ITALCERT (0426) Viale Sarca- 336 20126 - MILANO Italy

EN14387:2004 + A1:2008

Gas filters and combined filters

RETAILER STAMP

MAJ 28/04/2021