

Ref. 6PHP200

Non Vented Helmet General Use



The +

**PERFORMANCE:** High resistance (lateral deformation (LD), molten metal projection (MM), low temperatures -30°C) // ABS shell // Class 0: electrical insulation for low voltage installations up to 1000V a.c and 1500V d.c

**COMFORT:** Integrated safety glasses // Good balance and sensation of lightweight (450g) // Easy adjustment by ratchet // Preservation of the viewing area thanks to the short visor // 3D textile leather

**CUSTOMIZATION:** Add your logo (optional, upon request)  
Compatible with the badge holder (6POBA) and the shells (6MX3000NSI)

### DESCRIPTION

PHOENIX PRO safety helmet. ABS shell, polyethylene suspension points harness with 6 textile bands, ratchet size adjustment from 52 to 63 cm, short visor, integrated safety glasses with hard coated standard K and anti-fog standard N treatment, lateral slots, 3D textile sweatband, 4-point chin strap included with the helmet.

### SECTORS

- Heavy & process industries
- Mechanicals constructions
- Light Industries
- Regional/public authorities
- Infrastructure, building industry

### APPLICATIONS

Construction, industry...

### PURCHASE PACKAGING

Ref.	Size	Inner	Carton
6PHP200NSI	-		16

### SALES PACKAGING



Individual polybag

See also

### VARIANTS



6PHP400



6PHP160



6PHP800

## TECHNICAL FEATURES

<b>Shape</b>	Safety helmet	<b>Main risk</b>	Prevention against falling objects and head injuries and subsequent cranial trauma.
<b>Color</b>	Blue	<b>Value electric isolation</b>	1000V a.c / 1500V d.c
<b>Color 2</b>	Black	<b>Shell material</b>	ABS
<b>Weight</b>	450g	<b>Features</b>	ABS helmet 6-point LDPE harness Adjustment range from 52 to 63 cm Class 0: electrical insulation up to 1000V a.c and 1500V d.c
<b>Lens marking</b>	3-1.21 B	<b>Service life</b>	Manufacturing date indicated under the visor Usage 10 years without impact or damage
<b>Shade</b>	Clear	<b>Adjustment</b>	Rack adjustment from 52 to 63 cm
<b>Harness features</b>	Polyethylene 6-point harness Spider composed of 6 textile straps		

## STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate DPI/0497/2313

Delivered by CSI (0497) Cascina Traversagna- 21 20030 Senago (MI) Italy



EPI CAT. III

EN397:2012 + A1:2012

Industrial safety helmets

EN50365:2002

Electrically insulating helmets for use on low voltage installations (used for working on or near live parts of installations not exceeding 1,000 V AC or 1,500 V DC)

COVERPERF - Skincare



Dermatological safety approved after direct contact with the skin for 48 hours. No irritation was observed at the end of the test.