

Ref. 6REF220

Cartridges DIN

A2B2P3



The +

RD40 universal thread connection according to EN 148-1

PURCHASE PACKAGING

Référence	Taille	Sachet	Carton
6REF220NSI			60

SALES PACKAGING



Hangable individual pack

DESCRIPTION

Combined filter with special threaded connection DIN EN148-1 / RD-40 for A2B2 organic gases and vapours with boiling point above 65°C, and inorganic gases and vapours.

Can be used on all masks equipped with UNIVERSAL THREAD DIN148-1 / RD-40, and especially with PANAREA (20401) and EURMASK DIN (6EUR100NSI).

Body of the cartridge in HDPE, Filtering material in active carbon and filtering non-woven PP treated with anti-fungus and anti-bacteria products.

SECTORS

- Heavy & process industries
- Light Industries
- Infrastructure, building industry

APPLICATIONS

Organic gas and vapours with boiling point > 65°C - Inorganic gases and vapours - Toxic dusts, For regular and prolonged use in a dangerous environment: industrial maintenance, Fertilizer spreading, chemical industry, paint application, carpentry, wood industry, cement industry, metal cutting, fits with PANAREA, POLYCARBOMASK et PANORAMASK,

TECHNICAL FEATURES

Color	Black	Specifications	A2B2P3
Features	A2B2P3R Breathing resistance : <ul style="list-style-type: none">• 30 l/min : 1,70 mbar.• 95 l/min : 6,35 mbar.• Class 2 according to EN14387:2004	Main risk	Respiratory protection from gases and vapours
Other features	Body of the cartridge in HDPE, Filtering material in active carbon and filtering non-woven PP treated with anti-fungus and anti-bacteria products.		
Weight	265g		
Shape	DIN RD40 FIXATION		

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate **PPE060AT1591**

Delivered by ITALCERT (0426) Viale Sarca- 336 20126 - MILANO Italy



EN143:2000 / A1:2006

Particles filters

EN14387:2004 + A1:2008

Gas filters and combined filters

RETAILER STAMP

MAJ 04/03/2021