

# TECHNICAL DATASHEET

## **A2P3R FILTERS**

Ref. 6REF420

#### Cartridges Eurmask

A2P3 R

## The +

SUITABLE WITH NEW EURMASK 22102

#### PURCHASE PACKAGING

Référence

**Taille** 

**Sachet** Carton

6REF420NSI

16

#### SALES PACKAGING

>1

Multiple

#### **DESCRIPTION**

- Combined filter with special threaded connection for A2P3R organic gases and vapours with boiling point above 65 C, and fine toxic dusts, fumes, and mists.
- Must be used only by pair with NEW EURMASK 22102 (#7400)
- · Body of the cartridge in HDPE
- Filtering material: active carbon and filtering non woven PP.

#### **SECTORS**

Farming, silviculture and fishing

Heavy & process industries

Light Industries

Infrastructure, building industry

#### **APPLICATIONS**

Organic gas and vapours with boiling point > 65 C and fine toxic dusts For regular and prolonged use in a dangerous environment: industrial maintenance, Fertilizer spreading, chemical industry, paint application, carpentry, wood industry, cement industry, metal cutting ... Do not use in a place where oxygen

concentration is less than 17 vol. %

#### **TECHNICAL FEATURES**

Color Black Features A2P3R

Other features HDPE cartridge

Filtering material: active carbon and

filtering non woven PP

Weight 95 g Specifications A2P3 R Main risk

Respiratory protection against organic gas and vapours with boiling point > 65

C and fine toxic dusts

### STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate **PPE060AT1729**Delivered by ITALCERT (0426) Viale Sarca- 336 20126 - MILANO Italy

EPI CAT. III

EN14387:2004 + A1:2008 Gas filters and combined filters

RETAILER STAMP

MAJ 16/03/2021