

Ref. 6RES120

Non Reusable

FFP2 NR



The +

- Electrostatic filter media
- Exhalation valve: reduce breathing resistance and avoid fog and heat inside the mask
- Adjustable alu nose clip and comfortable nasal cushions
- Latex free elastic bands

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
6RES120NSI	-	-	20

SALES PACKAGING

>1

Multiple

DESCRIPTION

FFP2 half-mask made of non-woven polypropylene and polyester with valve, latex free synthetic rubber band, aluminum adjustable nose clip and PU foam nose pad, welded contour

SECTORS

- Heavy & process industries
- Light Industries
- Construction - finishing work
- DIY

APPLICATIONS

For occasional use in a very dusty environment. Protections against FFP1 and low toxic solid and liquid aerosols, such as woods, mineral oils, quartz, copper, aluminium, bacteria, fungi and mycobacterium tuberculosis (TB)., Textile industry, craft industry, metallurgical industry, mining industry, underground civil engineering, woodwork, welding, melting, metal cutting, hospitals, laboratories, medical controls

TECHNICAL FEATURES

Color	White	Harness features	Spandes & Nylon Elastic straps with 5 elasthan yarns
Color 2	Blue	Main risk	Respiratory protection from low toxic dusts and aerosol
Features	Shell mask with valve		
Other features	Half-mask in nonwoven polypropylene and polyester with valve. Latex free synthetic rubber band. Aluminium adjustable nose clip and PU foam nose pad. Welded contour.		
Weight	12g		
Shape	FFP2		
	Shell mask		
Specifications	FFP2 NR		

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate **715526**

Delivered by BSI Assurance UK Ltd (0086) Kitemark Court Davy Avenue Knowlhill Milton Keynes MK5 8PP United Kingdom



EPI CAT. III

EN149:2001 + A1:2009

FFP2 NR

Particle filtering half masks

RETAILER STAMP