

Cartridges Bayonet

Breathing resistance :
• 15 l/min : 1,45 mbar.
• 47,5 l/min : 5,10 mbar.



The +

BAYONET CONNECTION (b-lock)

PURCHASE PACKAGING

Référence	Taille	Sachet	Carton
6REF360NSI			18

SALES PACKAGING



Individual pack

DESCRIPTION

- Combined filter with bayonet connection for A2P3R organic gases and vapours with boiling point above 65°C, and fine toxic dusts, fumes, and mists.
- Quick bayonet release
- Must be used only by pair with ETNA (6ETN200NSI) & PANAREA TWIN (6PAN200NSI)
- Body of the cartridge in ABS
- Filtering material : active carbon and filtering non-woven PP.

SECTORS

- Heavy & process industries
- Light Industries
- Infrastructure, building industry
- Transport (excluding manufacturing) and logistics

APPLICATIONS

Organic gas and vapours with boiling point > 65°C
Toxic dusts, For regular and prolonged use in a dangerous environment: industrial maintenance, Fertilizer spreading, chemical industry, paint application, carpentry, wood industry, cement industry, metal cutting €|

TECHNICAL FEATURES

Features	
Other features	Filtering material : active carbon and filtering non-woven PP.
Weight	132g
Specifications	Breathing resistance : <ul style="list-style-type: none">• 15 l/min : 1,45 mbar.• 47,5 l/min : 5,10 mbar.• Class 2 according to EN14387:2004
Main risk	Aerosols and gases and vapours

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate **PPE060AT1696**

Delivered by ITALCERT (0426) Viale Sarca- 336 20126 - MILANO Italy



EN143:2000 / A1:2006

Particles filters

EN14387:2004 + A1:2008

Gas filters and combined filters

RETAILER STAMP