

Ref. 6REF430

Cartridges DIN

A1B1E1K1P3



The +

SUITABLE FOR NEW EURMASK 22102

PURCHASE PACKAGING

Référence	Taille	Sachet	Carton
6REF430NSI			16

SALES PACKAGING

>1

Multiple

DESCRIPTION

- Combined filter with special threaded connection for A1B1E1K1P3 organic gases and vapours with boiling point above 65°C, fine toxic dusts, mists and fumes.
- Must be used only by pair with NEW EURMASK 22102 (#7400)
- Body of the cartridge in HDPE
- Filtering material : active carbon and filtering non-woven PP

SECTORS

- Farming, silviculture and fishing
- Mechanicals constructions
- Chemical & pharmaceutical industries
- Maintenance
- Infrastructure, building industry
- Construction - finishing work

APPLICATIONS

Organic gas and vapours with boiling point > 65°C and toxic dusts
For regular and prolonged use in a dangerous environment: industrial maintenance, Fertilizer spreading, chemical industry, paint application, carpentry, wood industry, cement industry, metal cutting ...
Do not use in a place where oxygen concentration is less than 17 vol. %

TECHNICAL FEATURES

Color	Black
Features	A1B1E1K1P3 Breathing resistance : <ul style="list-style-type: none">• 15 l/min : 1,70 mbar.• 47,5 l/min : 5,65 mbar.• Class 1 according to EN14387:2004
Other features	Filtering material : active carbon and filtering non-woven PP.
Weight	99 g
Specifications	A1B1E1K1P3

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate **PPE060AT1621**

Delivered by ITALCERT (0426) Viale Sarca- 336 20126 - MILANO Italy



EPI CAT. III

EN143:2000 / A1:2006

Particles filters

EN14387:2004 + A1:2008

Gas filters and combined filters

RETAILER STAMP

MAJ 10/03/2021