coverguard®

TECHNICAL DATASHEET

FFP2 NR

Ref. 6RES120

Non Reusable







FFP2 NR



The +

Electrostatic filter media
Exhalation valve: reduce breathing
resistance and avoid fog and heat
inside the mask
Adjustable alu nose clip and
comfortable nasal cushions

Latex free elastic bands

PURCHASE PACKAGING

Ref. Size Inner Carton 6RES120NSI - 20

SALES PACKAGING

Hangable box

DESCRIPTION

FFP2 half-mask made of non-woven polypropylene and polyester with valve, latex free synthetic rubber band, aluminum adjustable nose clip and PU foam nose pad, welded contour

SECTORS

Heavy & process industries

Light Industries

Construction - finishing work

DIY

APPLICATIONS

For occasional use in a very dusty environment. Protections against FFP1 and low toxic solid and liquid aerosols, such as woods, mineral oils, quartz, copper, aluminium, bacteria, fungi and mycobacterium tuberculosis (TB)., Textile industry, craft industry, metallurgical industry, mining industry, underground civil engineering, woodwork, welding, melting, metal cutting, hospitals, laboratories, medical controls

TECHNICAL FEATURES

Shape Hull mask

Weight 12g

Specifica-tions FFP2 NR

Harness Spandes & Nylon Elastic straps with 5

features elastane yarns

Main risk Respiratory protection from low toxic

dusts and aerosol

Color White Color 2 Blue

Features Shell mask with valve

Other features Half-mask in nonwoven polypropylene and

polyester with valve.

Latex free synthetic rubber band. Aluminium adjustable nose clip and PU

foam nose pad. Welded contour.

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate CE 810304

Delivered by BSI Group The Netherlands B.V (2797) Say Building- John M. Keynesplein 9-1066 EP Amsterdam Netherlands

((

EPI CAT. III

EN149:2001 + A1:2009

Particle filtering half masks

FFP2 NR