

Ref. 6REF430

Cartridges Eurmask

A1B1E1K1P3



The +

SUITABLE FOR EURMASK 22102 / 22101

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
6REF430NSI	-		16

SALES PACKAGING

Hangable box

See also

VARIANTS



MO22130



MO22140



MO22150



MO22170



6REF410



6REF420

DESCRIPTION

* Combined filter with special threaded connection for A1B1E1K1P3 organic gases and vapours with boiling point above 65°C, fine toxic dusts, mists and fumes.

* Must be used only by pair with NEW EURMASK 22102 (#7400)

* Body of the cartridge in HDPE

* Filtering material : active carbon and filtering non-woven PP

SECTORS

Farming, silviculture and fishing

Mechanicals constructions

Chemical & pharmaceutical industries

Maintenance

Infrastructure, building industry

Construction - finishing work

APPLICATIONS

Organic gas and vapours with boiling point > 65°C and toxic dusts
For regular and prolonged use in a dangerous environment: industrial maintenance, Fertilizer spreading, chemical industry, paint application, carpentry, wood industry, cement industry, metal cutting ...
Do not use in a place where oxygen concentration is less than 17 vol. %

TECHNICAL FEATURES

Shape	Universal filter	Features	A1B1E1K1P3
Weight	99 g		Breathing resistance :
Specifications	A1B1E1K1P3		* 15 l/min : 1,70 mbar.
Main risk	Respiratory protection against organic gas and vapours with boiling point > 65°C and toxic dusts	Other features	* 47,5 l/min : 5,65 mbar.
			* Class 1 according to EN14387:2004
Color	Black		Filtering material : active carbon and filtering non-woven PP.

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate PPE060AT2466

Delivered by ITALCERT (0426) Viale Sarca- 336 20126 - MILANO Italy



EPI CAT. III

EN14387:2004 + A1:2008

Gas filters and combined filters