

Ref. 6RES130

Non Reusable

FFP3 NR



The +

Electrostatic filter media
 Exhalation valve: reduces breathing resistance and avoid fog and heat inside the mask
 Complete face seal for a better seal and optimal comfort
 Fabric and Spandex wide elastic strap with pull through adjustment buckles

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
6RES130NSI	-	-	20

SALES PACKAGING



Hangable box

DESCRIPTION

FFP3 disposable half-mask made of non-woven polypropylene and polyester with exhalation valve, fabric and rubber elastic strap, aluminum adjustable nose clip and PU foam total nose seal, welded contour

SECTORS

- Heavy & process industries
- Light Industries
- Infrastructure, building industry
- Construction - finishing work

APPLICATIONS

Occasional very dusty environments. Protection against solid and liquid aerosols FFP1, FFP2 and toxic. Chrome, manganese, nickel, platinum, strychnine, metal dust and fumes, viruses and enzymes, asbestos (maintenance and upkeep), textile industry, crafts, metallurgy, mining, underground work, carpentry, Welding, casting, metal cutting, hospitals, laboratories, medical checks, pharma, toxic waste, battery manufacturing (Ni-Cad).

TECHNICAL FEATURES

Shape	Hull mask	Color	Red
Weight	18g	Color 2	White
Specifications	FFP3 NR	Features	FFP3
Harness features	Spandex & nylon elastic straps with 7 elastane yarns		Shell mask in nonwoven polypropylene and polyester with valve.
Main risk	Respiratory protection from toxic dusts and aerosols		Wide fabric and rubber elastic straps. Aluminium adjustable nose clip and PU foam nose pad. Welded contour.

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate CE 810304

Delivered by BSI Group The Netherlands B.V (2797) Say Building- John M. Keynesplein 9- 1066 EP Amsterdam Netherlands



EPI CAT. III

EN149:2001 + A1:2009
FFP3 NR

Particle filtering half masks