coverguard

Technical datasheet

ADHARA

7ADHA10 Ref.

Harnesses & Belts





DESCRIPTION

Weight 2,33 kg Service 10 years

life

Webbing Aramid webbing width 44 belt

mm, withstand

temperatures up to 371°C Size

Attachment fall arrest attachment

points points:

> 1 dorsal D-ring and 2 sternal webbing loops. 2 positioning D-rings on

the belt.

Buckles Pass-Through buckles Adjustment&djustable shoulder,

chest and leg straps

PositioningAdjustable, with large comfortable back

support and tool holders

Universal

Capacity User of 140 kg

Breaking > 15kN strength

See also

Belted Harnesses











Specifically designed for use in welding and hot works

PURCHASE PACKAGING

Ref.

Carton

7ADHA10NSI

5

SALES PACKAGING



Individual pack

APPLICATIONS

- * Especially suited for use in welding and hot work environment
- * Full body harness with positioning belt, can be used in a fall arrest and / or positioning system

VARIANTS



7ANTA10

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate 2777/10362-04/E03-01 Delivered by SATRA Technology Europe Ltd (2777) Bracetown Business Park-Clonee- Dublin 15 Dublin Ireland



PPE Cat. III

EN ISO 15025:2002

Protection against flame. Method of test for limited flame spread

EN ISO 9150:1988

Determination of behaviour of materials on impact of small splashes of molten metal

EN361:2002

Full body harnesses