coverguard

TECHNICAL DATASHEET

Ref. 6TIFS00

Safety Glasses



AS UV 17G

The +

Wearing comfort

Airflex temples - engineered for optimal fit to any kind of head size
Lighweight (17g) for long wearing time

- Adjustable nose pads

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
6TIFS00NSI	-	10	100

SALES PACKAGING

Hangable individual polybag

See also





6TIFC00

DESCRIPTION

TIGER FIRST safety glasses. Smoke polycarbonate lens, anti-scratch coating, polycarbonate Airflex temples, adjustable nose pads

SECTORS

Heavy & process industries

Mechanicals constructions

Light Industries

Food-processing industry

Regional/public authorities

Maintenance

Infrastructure, building industry

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

For further information, please visit www.coverguard-safety.com

coverguard

TIGER FIRST

TECHNICAL FEATURES

Shape	Safety Glasses
Weight	17g
Lens	Polycarbonate, 1.6 mm
Lens marking	5 - 3,1 1FT
Frame	Polycarbonate
Frame marking	FT

Temple material	Polycarbonate
Temples	Not adjustable
Shade	Solar
Main risk	Use to prevent from chemicals, liquids
	splashes and from dust
Color	Grey
Features	AS anti-scratch coating

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate AC 21033

Delivered by CERTOTTICA (0530) Zona Industriale Villanova 32013 - Longarone (BL) Italy

CE	EPI CAT. II
EN166:2001	Specifications (optical quality, resistance to usual risks, mechanical risks, resistance to impacts)
EN 172:1994 + A1 :2000 + A2:2001	Sunglare filters for industrial use