

Ref. **9COBL**

Multipurpose

Low

Low shoes



S1P



0%
METAL

The +

- * Breathable upper and lining.
- * Footbridge supplying torsional rigidity.
- * Midsole with front protective covering.

PURCHASE PACKAGING

Ref.	Size	Carton
9COBL38	38	10
9COBL39	39	10
9COBL40	40	10
9COBL41	41	10
9COBL42	42	10
9COBL43	43	10
9COBL44	44	10
9COBL45	45	10
9COBL46	46	10
9COBL47	47	10

Some sizes may only be available in certain countries

See also

VARIANTS



9COBH

DESCRIPTION

Composite toecap
Antipenetration textile sole
External sole in double density PU/PU
Upper in Suede
Non woven lining
Padded belLow shoess
Padded collar

SECTORS

Infrastructure, building industry

Construction - finishing work

Transport (excluding manufacturing) and logistics

Services and distribution

APPLICATIONS

Luggage handler,
Delivery driver, ...

TECHNICAL FEATURES

Color	Grey	Insole	Attached, textile and foam
Color 2	Blue	Main assembly	Injected
Weight	587 g	Closing	Lacing closure
Upper	Suede leather / Mesh	Lining	Breathable 3D mesh
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **LEC F100343791**

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom



EPI CAT. II

EN ISO 20345:2011

S1P

SRC

Safety shoes

S1P Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol