

### Lanyards



#### DESCRIPTION

<b>Caract.</b>	Clearance distance: 6 m	<b>Breaking strength</b>	>15kN
<b>Weight</b>	1,18 kg		
<b>Service life</b>	10 years		
<b>Material</b>	Aramid webbing width 44 mm, withstand temperatures up to 371°C		
<b>Length</b>	1,5m		
<b>Connectors</b>	1 steel automatic karabiner and 1 x 50 mm steel scaffold hook		
<b>Force reduction</b>	< 6 kN		
<b>Capacity</b>	User of 100 kg		

#### STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate **2777/10363-02/E09-01**  
 Delivered by SATRA Technology Europe Ltd (2777) Bracetown Business Park-Clonee- Dublin 15 Dublin Ireland



PPE Cat. III

**EN ISO 15025:2002** Protection against flame. Method of test for limited flame spread

**EN ISO 9150:1988** Determination of behaviour of materials on impact of small splashes of molten metal

**EN 355:2002** Energy absorbers

### Absorbing Lanyards



#### The +

- \* Specifically designed for use in welding and hot works
- \* Twist-lock automatic karabiner at the absorber end for quick and safe connection

#### PURCHASE PACKAGING

<b>Ref.</b>	<b>Carton</b>
7ARAL10150	20

#### SALES PACKAGING



Individual pack

#### APPLICATIONS

- \* Especially suited for use in welding and hot works
- \* Shock absorbing lanyard designed to limit the forces in the body in the event of a fall

See also

#### VARIANTS



7ARD110