

Anchors

Temporary Anchors



The +

Provides horizontal mobility on I-beams

PURCHASE PACKAGING

| | |
|------------|--------|
| Ref. | Carton |
| 7BEAM20NSI | 15 |

SALES PACKAGING



Individual box

APPLICATIONS

- * Mobile anchor designed for horizontal use, attaching to I and H beams
- * Can be used overhead or at foot level, with a lanyard or Personal fall limiter

See also

VARIANTS



7BEAM10



7RIMO10

DESCRIPTION

| | | | |
|----------------|--|-----------------------------------|---|
| Caract. | Easily adjusts to the beam flange width by trigger. Secured with a pin. Can adjust to I beam flanges from 75 mm to 150 mm. | Service life | 10 years |
| Weight | 1,6 kg | Material | Aluminium, zinc-plated steel, stainless steel |
| | | Capacity Breaking strength | 1 user of 140 Kg > 22 kN |

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate 2777/10793-02/E02-02 Delivered by SATRA Technology Europe Ltd (2777) Bracetown Business Park-Clonee- Dublin 15 Dublin Ireland



PPE Cat. III

EN795:2012

Anchor devices

Type B