

Lanyards

Absorbing Lanyards



The +

- * Twist-lock automatic karabiner at the absorber end for quick and safe connection
- * Stitches protected by a transparent sleeve for durability

PURCHASE PACKAGING

Référence	Carton
7CORY10130	20
7CORY10180	20

SALES PACKAGING

Hangable individual pack

APPLICATIONS

- * Shock absorbing lanyard designed to limit the forces in the body in the event of a fall
- * Connecting element for a fall arrest system

See also

VARIANTS



7FAGU10

DESCRIPTION

Caract.	Loops with thimbles	Capacity	User of 100 kg
Other caract.	Clearance distance: 6 m	Breaking strength	>15kN
Weight	1,3m = 1,12 kg 1,8m = 1,15 kg		
Service life	10 years		
Material	Braided rope Ø 11 mm		
Length	1,3m/ 1,8m		
Connectors	1 steel automatic karabiner and 1 x 50 mm steel scaffold hook		
Force reduction	< 6 kN		

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate **2777/10963-01/E13-01**

Delivered by SATRA Technology Europe Ltd (2777) Bracetown Business Park- Clonee- Dublin 15 Dublin Ireland



EPI CAT. III

EN355:2002

Energy absorbers