

### Self Retracting Lifelines



Web SRL



### The +

Can be used horizontally, rated for a fall on sharp edge (radius 0,5 mm)

### PURCHASE PACKAGING

Ref.	Carton
7EDGS10NSI	4

### SALES PACKAGING



Individual box

### APPLICATIONS

- \* Vertical use and horizontal use with risk of a fall on sharp edge
- \* Allows freedom of movement and reduced clearance distance
- \* Connecting element in a fall arrest system

See also

### VARIANTS



MO71486



7PERS10

### DESCRIPTION

<b>Caract.</b>	Tested on sharp edge in accordance with VG 11.060 to secure areas near sharp edge ( $r \geq 0,5$ mm).	<b>Length</b>	6 m
<b>Weight</b>	2,7 kg	<b>Connectors</b>	Steel swivel snaphook with impact indicator at the end of the line
<b>Service life</b>	10 years	<b>Force reduction</b>	< 6 kN
<b>Housing</b>	Polymer housing with swivel eye and steel automatic karabiner	<b>Capacity</b>	User of 100 kg
<b>Lanyard</b>	Polyester webbing width 25 mm 6 m long	<b>Breaking strength</b>	>15 kN

### STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate 2777/10828-02/E06-01 Delivered by SATRA Technology Europe Ltd (2777) Bracetown Business Park- Clonee- Dublin 15 Dublin Ireland



PPE Cat. III

EN360:2002

Retractable type fall arresters

VG 11 CNB/P/11.060