coverguard®

Technical datasheet

ALTAI PRO

7ALTP40 Ref.

Accessories



ABS Shell,

LDPE cradle,

harness in polyester,

3-point chin strap in

strength between 15 and

Side slots for ear muffs,

polyester breaking

Headlamp clips

Textile headband,

6 point textile suspension life

Caract.

Color

CE





5 years from date of

from date of first use

manufacture and 3 years

Adjustable from 52 to 63

Helmets

The +

- * Dielectric protection 1000 V AC / 1500 V DC
- * Adjusment with rachet from 52 to 63 cm

PURCHASE PACKAGING

Ref. Carton 7ALTP40NSI 20

SALES PACKAGING



Individual polybag

APPLICATIONS

Maintenance at height, Telecom, Utility, work with

VARIANTS

See also

risk of fall from height, rescue

25 daN,

White

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate 2754/1747/158/03/20/0146 Delivered by ALIENOR CERTIFICATION (2754) ZA du Sanital - 21- rue Albert Einstein - 86100 CHATELLERAULT - France

PPE Cat. III

Weight

Service

Size

470 g

Adjustment Ratchet adjustment

cm

EN50365:2002

Electrically insulating helmets for use on low voltage installations (used for working on or near live parts of installations not exceeding 1,000 V AC or 1,500 V DC)

EN397:2012 + A1:2012

Industrial safety helmets





7ALTP60