

Lanyards

Absorbing Lanyards



The +

- * Suitable for use in ATEX environment
- * Aluminium connectors for lighter weight

PURCHASE PACKAGING

Ref.	Carton
7CASS10150	10

SALES PACKAGING



Individual pack

APPLICATIONS

- * Potentially explosive environments (ATEX)
- * Double leg shock absorbing lanyard designed to limit the forces in the body in the event of a fall
- * Provides 100% Tie-Off when the user is required to move from one anchor to another
- * Connecting element for a fall arrest system

DESCRIPTION

Service life	10 years
Length	1,5m
Force reduction	< 6 kN
Capacity	User of 100 kg
Breaking strength	>15kN
Material	Polyester antistatic webbing width 44 mm

Connectors	2 aluminium karabiner and 2 x 60 mm aluminium scaffold hooks
Weight	1,54 kg
Caract.	Certified for use in ATEX environment
Other caract.	Clearance distance: 6 m

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate 2777/10962-02/E04-01
Delivered by SATRA Technology Europe Ltd (2777) Bracetown Business Park- Clonee- Dublin 15 Dublin Ireland



PPE Cat. III

ATEX DIRECTIVE
2014/34/EU

II 2G Ex h IIc T6 Gb

EN355:2002

Energy absorbers

VG 11 CNB/P/11.063