

Ref. 7ARAL10

### Lanyards

### Absorbing Lanyards



1,5m

### The +

- \* Specifically designed for use in welding and hot works
- \* Twist-lock automatic karabiner at the absorber end for quick and safe connection

### PURCHASE PACKAGING

Ref.	Carton
7ARAL10150	20

### SALES PACKAGING



Individual polybag

### APPLICATIONS

- \* Especially suited for use in welding and hot works
- \* Shock absorbing lanyard designed to limit the forces in the body in the event of a fall

See also

### VARIANTS



7ARDI10

### DESCRIPTION

<b>Caract.</b>	Clearance distance: 6 m	<b>Connectors</b>	1 steel automatic karabiner and 1 x 50 mm steel scaffold hook
<b>Weight</b>	1,18 kg	<b>Force</b>	< 6 kN
<b>Service life</b>	10 years	<b>reduction</b>	
<b>Material</b>	Aramid webbing width 44 mm, withstand temperatures up to 371°C	<b>Capacity</b>	User of 100 kg
<b>Length</b>	1,5m	<b>Breaking strength</b>	>15kN

### STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate **2777/10363-03/E01-01**  
Delivered by SATRA Technology Europe Ltd (2777) Bracetown Business Park-Clonee- Dublin 15 Dublin Ireland



PPE Cat. III

EN ISO 15025:2002	Protection against flame. Method of test for limited flame spread
EN ISO 9150:1988	Determination of behaviour of materials on impact of small splashes of molten metal
EN355:2002	Energy absorbers