

Lanyards



DESCRIPTION

Caract.	Clearance distance: 6 m	Connectors	1 steel automatic karabiner and 2 x 50 mm steel scaffold hook
Weight	1,84 kg	Force	< 6 kN
Service life	10 years	reduction	
Material	Aramid webbing width 44 mm, withstand temperatures up to 371°C	Capacity	User of 100 kg
Length	1,5m	Breaking strength	>15kN

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate **2777/10962-03/E06-01**
Delivered by SATRA Technology Europe Ltd (2777) Bracetown Business Park- Clonee- Dublin 15 Dublin Ireland



PPE Cat. III

EN ISO 15025:2002 Protection against flame. Method of test for limited flame spread

EN ISO 9150:1988 Determination of behaviour of materials on impact of small splashes of molten metal

EN355:2002 Energy absorbers

VG 11 CNB/P/11.063

Absorbing Lanyards



The +

- * Specifically designed for use in welding and hot works
- * Twist-lock automatic karabiner at the absorber end for quick and safe connection

PURCHASE PACKAGING

Ref.	Carton
7ARDI10150	10

SALES PACKAGING



Individual polybag

APPLICATIONS

- * Especially suited for use in welding and hot works
- * Double leg shock absorbing lanyard designed to limit the forces in the body in the event of a fall
- * Provides 100% Tie-Off when the user is required to move from one anchor to another
- * Connecting element for a fall arrest system

See also

VARIANTS



7ARAL10