

Lanyards

Absorbing Lanyards



The +

- * Twist-lock automatic karabiner at the absorber end for quick and safe connection
- * Stitches protected by a transparent sleeve for durability

PURCHASE PACKAGING

Référence	Carton
7FAGU10100	10
7FAGU10130	10
7FAGU10180	10

SALES PACKAGING

Hangable individual pack

APPLICATIONS

- * Double leg shock absorbing lanyard designed to limit the forces in the body in the event of a fall
- * Provides 100% Tie-Off when the user is required to move from one anchor to another
- * Connecting element for a fall arrest system

See also

VARIANTS



7CORY10



7PIRU10

DESCRIPTION

Caract.	Loops with thimbles	Force	< 6 kN
Other caract.	Clearance distance: 6 m	reduction	
Weight	1 m = 1,74 kg 1,3 m = 1,86 kg 1,8 m = 1,92 kg	Capacity	User of 100 kg
Service life	10 years	Breaking strength	>15kN
Material	Braided rope Ø 11 mm		
Length	1 m / 1,3 m / 1,8 m		
Connectors	1 steel automatic karabiner and 2 x 50 mm steel scaffold hook		

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate **2777/10964-01/E11-01**

Delivered by SATRA Technology Europe Ltd (2777) Bracetown Business Park- Clonee- Dublin 15 Dublin Ireland



EPI CAT. III

EN355:2002

Energy absorbers

VG 11 CNB/P/11.063