

Lanyards

Absorbing Lanyards



1,3m/
1,8m

The +

- * Twist-lock automatic karabiner at the absorber end for quick and safe connection
- * Stitches protected by a transparent sleeve for durability

PURCHASE PACKAGING

Ref.	Carton
7CORY10130	20
7CORY10180	20

SALES PACKAGING



Individual polybag

APPLICATIONS

- * Shock absorbing lanyard designed to limit the forces in the body in the event of a fall
- * Connecting element for a fall arrest system

See also

VARIANTS



7FAGU10

DESCRIPTION

Caract.	Loops with thimbles	Connecto	1 steel automatic
Other	Clearance distance: 6 m	r-s	karabiner and 1 x 50 mm
caract.			steel scaffold hook
Weight	1,3m = 1,12 kg	Force	< 6 kN
	1,8m = 1,15 kg	reduction	
Service	10 years	Capacity	User of 100 kg
life		Breaking	>15kN
Material	Polyamide braided rope	strength	
	Ø 11 mm		
Length	1,3m/ 1,8m		

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate 2777/10963-03/E07-01. Delivered by SATRA Technology Europe Ltd (2777) Bracetown Business Park-Clonee- Dublin 15 Dublin Ireland



PPE Cat. III

EN355:2002

Energy absorbers