

Lanyards

Absorbing Lanyards



The +

- * Aluminium connectors for lighter weight
- * Stitches protected by a transparent sleeve for durability

PURCHASE PACKAGING

Référence	Carton
7PIRU10130	10
7PIRU10180	10

SALES PACKAGING

Hangable individual pack

APPLICATIONS

- * Double leg shock absorbing lanyard designed to limit the forces in the body in the event of a fall
- * Provides 100% Tie-Off when the user is required to move from one anchor to another
- * Connecting element for a fall arrest system

See also

VARIANTS



7FAGU10

DESCRIPTION

Caract.	Loops with thimbles	Capacity	User of 100 kg
Other caract.	Clearance distance: 6 m	Breaking strength	>15kN
Weight	1,3 m = 1,7 kg 1,8 m = 1,8 kg		
Service life	10 years		
Material	Braided rope Ø 11 mm		
Length	1,3m/ 1,8m		
Connectors	1 aluminium snaphook and 2 x 60 mm aluminium scaffold hooks		
Force reduction	< 6 kN		

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate **2777/10964-01/E11-01**

Delivered by SATRA Technology Europe Ltd (2777) Bracetown Business Park- Clonee- Dublin 15 Dublin Ireland



EPI CAT. III

EN355:2002

Energy absorbers

VG 11 CNB/P/11.063