

Lanyards

Absorbing Lanyards



The +

- * Validated for use near sharp edge
- * Twist-lock automatic karabiner at the absorber end for quick and safe connection
- * Stitches protected by a transparent sleeve for durability

PURCHASE PACKAGING

| Référence | Carton |
|------------|--------|
| 7NYSS10150 | 20 |

SALES PACKAGING

Hangable individual pack

APPLICATIONS

- * Shock absorbing lanyard designed to limit the forces in the body in the event of a fall
- * Connecting element for a fall arrest system

See also

VARIANTS



7OLEA10

DESCRIPTION

| | | | |
|----------------------|---|--------------------------|----------------|
| Caract. | Edge tested for protection in case of fall on sharp edge. Complies with VG 11.074 (r>=0,5 mm) | Force reduction | < 6 kN |
| Other caract. | Loops with thimbles Clearance distance: 6 m | Capacity | User of 100 kg |
| Weight | 1,16 kg | Breaking strength | >15kN |
| Service life | 10 years | | |
| Material | Braided rope Ø 11 mm | | |
| Length | 1,5m | | |
| Connectors | 1 steel automatic karabiner and 1 x 50 mm steel scaffold hook | | |

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate **2777/10963-01/E13-01**
Delivered by SATRA Technology Europe Ltd (2777) Bracetown Business Park-Clonee- Dublin 15 Dublin Ireland



EPI CAT. III

EN355:2002

Energy absorbers

VG 11 CNB/P/11.074