

Ref. 7OLEA10

Lanyards

Absorbing Lanyards



1,5m



The +

- * Validated for use near sharp edge
- * Twist-lock automatic karabiner at the absorber end for quick and safe connection
- * Stitches protected by a transparent sleeve for durability

DESCRIPTION

Caract.	Tested on sharp edge in accordance with VG 11.074 to secure areas near sharp edge ($r \geq 0,5$ mm)	Length	1,5m
Other caract.	Loops with thimbles	Connectors	1 steel automatic karabiner and 2 x 50 mm steel scaffold hooks
Weight	Clearance distance: 6 m	Force reduction	< 6 kN
Service life	1,92 kg	Capacity	User of 100 kg
Material	10 years	Breaking strength	>15kN
	Polyamide braided rope Ø 11 mm		

PURCHASE PACKAGING

Ref.	Carton
7OLEA10150	10

SALES PACKAGING



Individual polybag

APPLICATIONS

- * Construction, industry... areas with risks of falling on sharp edges
- * Double leg shock absorbing lanyard designed to limit the forces in the body in the event of a fall
- * Provides 100% Tie-Off when the user is required to move from one anchor to another
- * Connecting element for a fall arrest system

See also

VARIANTS



7NYSS10

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate **2777/10964-03/E06-01** Delivered by SATRA Technology Europe Ltd (2777) Bracetown Business Park- Clonee- Dublin 15 Dublin Ireland



PPE Cat. III

EN355:2002

Energy absorbers

VG 11 CNB/P/11.074

VG 11 CNB/P/11.063