

Lanyards

Absorbing Lanyards



The +

- * Elastic webbing reduces length when not in tension and limits trip and snagging hazard
- * Aluminium connectors for lighter weight

PURCHASE PACKAGING

Référence	Carton
7SALI10200	10

SALES PACKAGING

Hangable individual pack

APPLICATIONS

- * Double leg shock absorbing lanyard designed to limit the forces in the body in the event of a fall
- * Provides 100% Tie-Off when the user is required to move from one anchor to another
- * Connecting element for a fall arrest system

See also

VARIANTS



7LARI10

DESCRIPTION

Caract.	Protected loops for durability	Force reduction	< 6 kN
Other caract.	Clearance distance: 6 m	Capacity	User of 100 kg
Weight	1,92 kg	Breaking strength	>15kN
Service life	10 years		
Material	Tubular polyester webbing width 44mm		
Length	1,4m → 2m		
Connectors	1 aluminium snaphook and 2 x 60 mm aluminium scaffold hooks		

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate **2777/10960-01/E10-01**
 Delivered by SATRA Technology Europe Ltd (2777) Bracetown Business Park- Clonee- Dublin 15 Dublin Ireland



EPI CAT. III

EN355:2002

Energy absorbers

VG 11 CNB/P/11.063