

Ref. **9ALTH**

Multipurpose

High

High shoes



S3



HRO

0%
METAL

The +

- * Padded collar and bellows tongue for snug fit.
- * Heel scuff cap.
- * Shock absorbing EVA midsole.

PURCHASE PACKAGING

Ref.	Size	Carton
9ALTH36	36	
9ALTH37	37	10
9ALTH38	38	10
9ALTH39	39	10
9ALTH40	40	10
9ALTH41	41	10
9ALTH42	42	10
9ALTH43	43	10
9ALTH44	44	10
9ALTH45	45	10
9ALTH46	46	10
9ALTH47	47	10
9ALTH48	48	

Some sizes may only be available in certain countries

DESCRIPTION

Composite toecap
Antipenetration textile Wellmax sole
External sole in double density EVA/Rubber
Upper in crazy horse leather
Breathable mesh lining
Reinforcement : back in PVC

SECTORS

- Mining
- Extracting Oil and Gas
- Energy (production and distribution)
- Infrastructure, building industry

APPLICATIONS

Builder,
Slater,
Ramp agent,
Luggage handler,
Site supervisor,
Dockers, ...

See also

VARIANTS



9ALTL

TECHNICAL FEATURES

Color	Brown	Main assembly	Cemented
Color 2	Beige	Reinforcement material	Anti-abrasion Stark®
Upper	Full grain leather / Mesh	Reinforcement location	Heel
Toecap	Composite	Closing	Lacing closure
Puncture resistant sole	Textile	Weight	603 g
Midsole	EVA	Lining	Breathable 3D mesh
Outsole	Rubber nitrile		
Insole	Removable, textile and foam		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate ITASLNB21013927

Delivered by INTERTEK Italia S.p.A. (2575) Via Guido Miglioli 2/A 20063 Cernusco sul Naviglio - Milano (MI) Italy



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRA

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

HRO

Heat contact resistant outsole (60 seconds at 300°C)