

Ref. **9ACSA**

Synthetic Boots

PVC

Boots



S5



### The +

- \* Extra ankles support.
- \* Sole red plate for more confort.
- \* Durable shaft and tear resistance.

#### PURCHASE PACKAGING

Ref.	Size	Carton
9ACSA39	39	6
9ACSA40	40	6
9ACSA41	41	6
9ACSA42	42	6
9ACSA43	43	6
9ACSA44	44	6
9ACSA45	45	6
9ACSA46	46	6
9ACSA47	47	6
9ACSA48	48	6

*Some sizes may only be available in certain countries*

#### DESCRIPTION

Steel toecap  
Steel antipenetration sole  
External sole in black PVC  
Black PVC upper  
Grey polyester lining

#### SECTORS

Heavy & process industries

Light Industries

Food-processing industry

Regional/public authorities

## TECHNICAL FEATURES

Color	Black
Weight	1200 g
Upper	Acifort®
Toecap	Steel
Puncture resistant sole	Steel
Outsole	Acifort®
Lining	Polyester

## INSTRUCTION FOR USE AND STORAGE

**Instructions for use**

These boots can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

**Storage instructions**

Place the boots, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

**Washing instructions**

Regularly clean the boots by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **839**

Delivered by SATRA Technology Centre Ltd (0321) Wyndham Way Telford Way Kettering- Northamptonshire- NN16 8SD United Kingdom



EPI CAT. II

EN ISO 20345:2011

S5

SRA

Safety shoes

**S5** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Spiked outsole + Puncture resistant midsole

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol