

Ref. **9ALTL**

Multipurpose

Low

Low shoes



The +

- * Padded collar and bellows tongue for snug fit.
- * Heel scuff cap.
- * Shock absorbing EVA midsole.

PURCHASE PACKAGING

Ref.	Size	Carton
9ALTL36	36	
9ALTL37	37	10
9ALTL38	38	10
9ALTL39	39	10
9ALTL40	40	10
9ALTL41	41	10
9ALTL42	42	10
9ALTL43	43	10
9ALTL44	44	10
9ALTL45	45	10
9ALTL46	46	10
9ALTL47	47	10

Some sizes may only be available in certain countries

See also

DESCRIPTION

Composite toecap
 Antipenetration textile Wellmax sole
 External sole in double density EVA/Rubber
 Upper in crazy horse leather
 Breathable mesh lining
 Reinforcement : back in PVC

SECTORS

- Mining
- Extracting Oil and Gas
- Energy (production and distribution)
- Infrastructure, building industry

APPLICATIONS

Builder,
 Slater,
 Ramp agent,
 Luggage handler,
 Site supervisor,
 Docker, ...

VARIANTS



9ALTH

TECHNICAL FEATURES

Color	Brown	Insole	Removable, textile and foam
Color 2	Beige	Main assembly	Cemented
Weight	603 g	Reinforcement material	Anti-abrasion Stark®
Upper	Full grain leather / Mesh	Reinforcement location	Heel
Toecap	Composite	Closing	Lacing closure
Puncture resistant sole	Textile	Lining	Breathable 3D mesh
Midsole	EVA		
Outsole	Rubber nitrile		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate ITASLNB21013927

Delivered by INTERTEK Italia S.p.A. (2575) Via Guido Miglioli 2/A 20063 Cernusco sul Naviglio - Milano (MI) Italy



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRA

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

HRO

Heat contact resistant outsole (60 seconds at 300°C)