

Ref. **9AQUA**

Outdoor

High

High shoes



S3



The +

*Water repellent.

*Padded collar, ankles bellows tongue for snug fit.

*Footbridge torsional rigidity.

PURCHASE PACKAGING

Ref.	Size	Carton
9AQUA38	38	10
9AQUA39	39	10
9AQUA40	40	10
9AQUA41	41	10
9AQUA42	42	10
9AQUA43	43	10
9AQUA44	44	10
9AQUA45	45	10
9AQUA46	46	10
9AQUA47	47	10

Some sizes may only be available in certain countries

DESCRIPTION

Breathable composite toecap
Antipenetration textile sole
External sole in double density PU/PU
Upper in crazy horse leather
Lining : Waterproof membrane
Reinforcement : front and back in PU
705 g per shoe in size 8

SECTORS

Mining

Extracting Oil and Gas

Energy (production and distribution)

Infrastructure, building industry

APPLICATIONS

Builder,
Slater,
Ramp agent,
Luggage handler,
Site supervisor,
Dockers, ...

TECHNICAL FEATURES

Color	Black	Outsole	PU
Color 2	Blue	Insole	Removable, textile and foam
Weight	705 g	Main assembly	Injected
Upper	Full grain leather	Closing	Lacing closure
Toecap	Composite	Lining	Waterproof and breathable membrane /
Toecap 2	breathable		Moisture wicking non-woven membrane
Puncture resistant sole	Textile		
Midsole	PU		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **LEC F100379242**

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

WR

Water repellent shoe