

Ref. **9AZUH10**

Multipurpose

High

High shoes



The +

- * Midsole with front protective covering.
- * Defined heel for better safety especially on ladders.
- * EVA insole, breathable and anti-odor.
- * Reflective stripe with multiple faces.

PURCHASE PACKAGING

Ref.	Size	Carton
9AZUH10036	36	6
9AZUH10037	37	6
9AZUH10038	38	6
9AZUH10039	39	6
9AZUH10040	40	6
9AZUH10041	41	6
9AZUH10042	42	6
9AZUH10043	43	6
9AZUH10044	44	6
9AZUH10045	45	6
9AZUH10046	46	6
9AZUH10047	47	6
9AZUH10048	48	6

Some sizes may only be available in certain countries

See also

VARIANTS



9AZUL10

DESCRIPTION

AZURITE II shoes are made of waterproof grain leather. Its outsole is non-slip and resistant to oils and hydrocarbons and resists slipping on ceramic and steel floors. Its insole has an anti-odor treatment. PU reinforcement at the front of the foot. Non-woven lining and padded gusset.

SECTORS

Light Industries

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

TECHNICAL FEATURES

Color	Black	Insole	Removable, perforated EVA and anti-odor
Weight	658 g	Main assembly	Injected
Upper	Grain leather	Closing	Lacing closure
Toecap	Steel	Lining	Moisture wicking non-woven membrane
Puncture resistant sole	Steel		
Midsole	PU		
Outsole	PU		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate LECFI00381124

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

ESD

Electrostatic discharge shoe (CEI EN 61340-4-3 standard)