

Self Retracting Lifelines



Personal SRL



The +

- * Can be used in any direction
- * Can be connected at foot level
- * 140 kg user capacity in fall factor 0, 1 and 2

PURCHASE PACKAGING

Ref.	Carton
7SOLA10NSI	4

SALES PACKAGING



Individual box

APPLICATIONS

- * Vertical and horizontal use
- * Allows freedom of movement and reduced clearance distance
- * Connecting element in a fall arrest system

DESCRIPTION

Caract.	Can be used in fall factor 0, 1 and 2. Capacity 140 kg, even in factor 2.	Lanyard	2 m long UHMWPE webbing width 20 mm with 60 mm aluminium scaffold hook
Other caract.	Clearance distance: 4 m	Length	2 m
Weight	1,2 kg	Force reduction	< 6 kN
Service life	10 years	Capacity Breaking strength	User of 140 kg >15 kN
Housing	Polymer housing with swivel eye and Aluminium automatic karabiner		

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate **2777/14604-02/E01-01**
Delivered by SATRA Technology Europe Ltd (2777) Bracetown Business Park- Clonee- Dublin 15 Dublin Ireland



PPE Cat. III

EN360:2002

Retractable type fall arresters