

Ref. **9AGH010**

Multipurpose

High

High shoes



The +

- \* Value for money
- \* Full grain leather upper
- \* Reflective stripe with multiple faces
- \* PU2D injected outsole
- \* Defined and raised heel

### PURCHASE PACKAGING

Ref.	Size	Carton
9AGH010034	34	10
9AGH010035	35	10
9AGH010036	36	10
9AGH010037	37	10
9AGH010038	38	10
9AGH010039	39	10
9AGH010040	40	10
9AGH010041	41	10
9AGH010042	42	10
9AGH010043	43	10
9AGH010044	44	10
9AGH010045	45	10
9AGH010046	46	10
9AGH010047	47	10
9AGH010048	48	10
9AGH010049	49	10

*Some sizes may only be available in certain countries*

### DESCRIPTION

AGATE II is an ankle safety shoe. Its full grain upper brings a better resistance and breathability than split leather whereas the ankle padding provides supports to the wearer. The polyester mesh lining improves breathability and hence comfort. The out & mid-soles are made of injected polyurethane of different density which balance comfort and durability. This shoe features a steel toe-cap and plate for protection against puncture and fall of heavy objects. The retro-reflective band with patterns improves safety of wearers while in dark environments. AGATE II is equipped with a cleated outsole with good adhesion properties. Ideal for indoor as well as outdoor works.

### SECTORS

Infrastructure, building industry

Construction - finishing work

Transport (excluding manufacturing) and logistics

Services and distribution

### APPLICATIONS

Luggage handler,  
Delivery driver, ...

See also

### VARIANTS



9AGL010

## TECHNICAL FEATURES

Color	Black	Main assembly	Injected
Weight	622 g	Closing	Lacing closure
Upper	Full grain leather	Lining	Moisture wicking non-woven membrane
Toecap	Steel		
Puncture resistant sole	Steel	Defined heel	
Midsole	PU		
Outsole	PU		
Insole	Removable, textile and foam		

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 5 years is not recommended.

## Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/05/23/0869

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2022

S3

Safety shoes

**S3** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance