

Ref. **9ASTL**

Multipurpose

Low

Low shoes



### The +

- \* Lightweight for use all day long.
- \* Breathable upper and lining.
- \* Flexibility.

### PURCHASE PACKAGING

Ref.	Size	Carton
9ASTL36	36	
9ASTL37	37	10
9ASTL38	38	10
9ASTL39	39	10
9ASTL40	40	10
9ASTL41	41	10
9ASTL42	42	10
9ASTL43	43	10
9ASTL44	44	10
9ASTL45	45	10
9ASTL46	46	10
9ASTL47	47	10

*Some sizes may only be available in certain countries*

*See also*

### DESCRIPTION

Composite toecap  
 Antipenetration textile Wellmax sole  
 External sole in PU  
 Upper in crazy horse leather  
 Breathable mesh lining

### SECTORS

- Infrastructure, building industry
- Construction - finishing work
- Transport (excluding manufacturing) and logistics
- Services and distribution

### APPLICATIONS

Luggage handler,  
 Delivery driver, ...

### VARIANTS



9ASTH

## TECHNICAL FEATURES

Color	Black	Lining	Breathable 3D mesh
Weight	506 g		
Upper	Pull-up leather		
Toecap	Composite		
Puncture resistant sole	Textile		
Outsole	PU		
Insole	Removable, textile and foam		
Closing	Lacing closure		

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **LEC F100340789**

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

**S3** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol