

Ref. **9ALL160**

Multipurpose

Low

Low shoes



### The +

- \*Flexible and water repellent upper.
- \*Scuff cap front and back.
- \*Insole foam with pads: comfort.

#### PURCHASE PACKAGING

Ref.	Size	Carton
9ALL160037	37	6
9ALL160038	38	6
9ALL160039	39	6
9ALL160040	40	6
9ALL160041	41	6
9ALL160042	42	6
9ALL160043	43	6
9ALL160044	44	6
9ALL160045	45	6
9ALL160046	46	6
9ALL160047	47	6

*Some sizes may only be available in certain countries*

See also

#### VARIANTS



9ALU160

#### DESCRIPTION

ALUNI combines lightness and a sporty look. Equipped with an EVA / rubber nitrile outsole, this sneaker is remarkably flexible. The HI-POLY foam of the insole and its pads guarantee great wearing comfort. Its Oxford fabric upper is waterproof.

#### SECTORS

Light Industries

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

## TECHNICAL FEATURES

Color	Black	Insole	Foam with pads
Color 2	Yellow	Reinforcement material	TPU
Weight	501 g	Closing	Lacing closure
Upper	Oxford	Lining	Breathable 3D mesh
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	EVA		
Outsole	Rubber nitrile		

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/07/21/1155

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

**S3** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol