

Ref. **9AQUA**

Outdoor

High

High shoes



The +

\*Water repellent.

\*Padded collar, ankles bellows tongue for snug fit.

\*Footbridge torsional rigidity.

### PURCHASE PACKAGING

Ref.	Size	Carton
9AQUA38	38	10
9AQUA39	39	10
9AQUA40	40	10
9AQUA41	41	10
9AQUA42	42	10
9AQUA43	43	10
9AQUA44	44	10
9AQUA45	45	10
9AQUA46	46	10
9AQUA47	47	10

*Some sizes may only be available in certain countries*

### DESCRIPTION

Breathable composite toecap  
Antipenetration textile sole  
External sole in double density PU/PU  
Upper in crazy horse leather  
Lining : Waterproof membrane  
Reinforcement : front and back in PU  
705 g per shoe in size 8

### SECTORS

Mining  
Extracting Oil and Gas  
Energy (production and distribution)  
Infrastructure, building industry

### APPLICATIONS

Builder,  
Slater,  
Ramp agent,  
Luggage handler,  
Site supervisor,  
Dock, ...

## TECHNICAL FEATURES

Color	Black	Outsole	PU
Color 2	Blue	Insole	Removable, textile and foam
Weight	705 g	Main assembly	Injected
Upper	Full grain leather	Closing	Lacing closure
Toecap	Composite	Lining	Waterproof and breathable membrane /
Toecap 2	breathable		Moisture wicking non-woven membrane
Puncture resistant sole	Textile		
Midsole	PU		

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/09/24/2216 EXT 04/09/24

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

WR

Water repellent shoe

EN ISO 20345:2022

Safety shoes

S7S

**S7S** Basic requirements: a protective toe cap resistant to an impact of 200 Joule and a crushing of 15,000 Newton and:- closed heel area- antistatic properties- energy-absorbing capacity of the heel Puncture resistance: - Sole puncture resistance (1100 Newton) - Non-metallic insert, 3.0mm diameter puncture needle- resistance to penetration and water absorption of the upper- puncture resistance according to type- cleated outsole - non-metallic insert type PS+ Water resistance of the entire shoe

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance