

Ref. **9ASTH**

Multipurpose

High

High shoes



S3



0% METAL

The +

- * Lightweight for use all day long.
- * Breathable upper and lining.
- * Flexibility for easier kneeling at work.

PURCHASE PACKAGING

Ref.	Size	Carton
9ASTH37	37	10
9ASTH38	38	10
9ASTH39	39	10
9ASTH40	40	10
9ASTH41	41	10
9ASTH42	42	10
9ASTH43	43	10
9ASTH44	44	10
9ASTH45	45	10
9ASTH46	46	10
9ASTH47	47	10

Some sizes may only be available in certain countries

See also

VARIANTS



9ASTL

DESCRIPTION

Composite toecap
 Antipenetration textile Wellmax sole
 External sole in PU
 Upper in crazy horse leather
 Breathable mesh lining

SECTORS

Infrastructure, building industry

Construction - finishing work

Transport (excluding manufacturing) and logistics

Services and distribution

APPLICATIONS

Luggage handler,
 Delivery driver, ...

TECHNICAL FEATURES

Color	Black	Lining	Breathable 3D mesh
Weight	539 g		
Upper	Pull-up leather		
Toecap	Composite		
Puncture resistant sole	Textile		
Outsole	PU		
Insole	Removable, textile and foam		
Closing	Lacing closure		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **LEC F100340789**

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol