

Ref. **9ALU160**

Multipurpose

High

High shoes



The +

- *Flexible and water repellent upper.
- *Scuff cap front and back.
- *Insole foam with pads: comfort.

PURCHASE PACKAGING

Ref.	Size	Carton
9ALU160036	36	6
9ALU160037	37	6
9ALU160038	38	6
9ALU160039	39	6
9ALU160040	40	6
9ALU160041	41	6
9ALU160042	42	6
9ALU160043	43	6
9ALU160044	44	6
9ALU160045	45	6
9ALU160046	46	6
9ALU160047	47	6
9ALU160048	48	6

Some sizes may only be available in certain countries

See also

DESCRIPTION

ALUNI combines lightness and a sporty look. Equipped with an EVA / rubber nitrile outsole, this sneaker is remarkably flexible. The HI-POLY foam of the insole and its pads guarantee great wearing comfort. Its Oxford fabric upper is waterproof.

SECTORS

Light Industries

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

VARIANTS



9ALL160

TECHNICAL FEATURES

Weight	522 g	Insole	Foam with pads
Color	Black	Reinforcement material	TPU
Color 2	Yellow	Reinforcement location	Heel / Front
Upper	Oxford	Closing	Lacing closure
Toecap	Composite	Lining	Breathable 3D mesh
Puncture resistant sole	Textile		
Midsole	EVA		
Outsole	Rubber nitrile		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 5 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/09/24/2237

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

COVERPERF - Damping



Shoes tested in a certified laboratory (CTC) offering excellent damping. Over 25% of the impact force is absorbed by the sole.

EN ISO 20345:2022

S3S

Safety shoes

S3S Basic requirements: a protective toe cap resistant to an impact of 200 Joule and a crushing of 15,000 Newton+ closed heel area- antistatic properties- energy-absorbing capacity of the heel Puncture resistance:- Resistance of the sole to puncture (min.1100 N and individual value \geq 950 N) - Non-metallic insert, 3.0mm diameter puncture needle+ non-metallic insert type PS - resistance to penetration and water absorption of the upper- puncture resistance according to type- cleated outsole

FO

Hydrocarbons resistance