

Ref. **9AVEH**

Outdoor

High

High shoes



S3



0%  
METAL

The +

- \* Padding for snug fit.
- \* Defined heel for better safety especially on ladders.

### PURCHASE PACKAGING

Ref.	Size	Carton
9AVEH38	38	10
9AVEH39	39	10
9AVEH40	40	10
9AVEH41	41	10
9AVEH42	42	10
9AVEH43	43	10
9AVEH44	44	10
9AVEH45	45	10
9AVEH46	46	10
9AVEH47	47	10

*Some sizes may only be available in certain countries*

See also

### VARIANTS



9AVEL

### DESCRIPTION

Composite toecap  
Antipenetration textile sole  
External sole in double density PU/PU  
Breathable non woven Tybrelle lining  
Padded Collar with PU  
Upper in full grain leather  
Padded bellows in black split cow leather

### SECTORS

Infrastructure, building industry

Construction - finishing work

Transport (excluding manufacturing) and logistics

Services and distribution

### APPLICATIONS

Luggage handler,  
Delivery driver, ...

## TECHNICAL FEATURES

Color	Black	Main assembly	Injected
Weight	603 g	Closing	Lacing closure
Upper	Full grain leather	Lining	Moisture wicking non-woven membrane
Toecap	Composite	Defined heel	
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		
Insole	Attached, textile and foam		

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate LECFI00377774

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

**S3** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol