

Ref. **9BOSC10**

Indoor and dry environments

Low

Sandals



### The +

\*Open shoe to be protected without suffering from heat.

\*Defined heel for better safety especially on ladders.

### PURCHASE PACKAGING

Ref.	Size	Carton
9BOSC10035	35	10
9BOSC10036	36	10
9BOSC10037	37	10
9BOSC10038	38	10
9BOSC10039	39	10
9BOSC10040	40	10
9BOSC10041	41	10
9BOSC10042	42	10
9BOSC10043	43	10
9BOSC10044	44	10
9BOSC10045	45	10
9BOSC10046	46	10
9BOSC10047	47	10
9BOSC10048	48	10

*Some sizes may only be available in certain countries*

### DESCRIPTION

BOSCO II is a shoe in micro-perforated full grain leather with a breathable 3D mesh lining which increases breathability of the shoe for a sustainable comfort. This model is equipped of a steel toe cap and a steel puncture resistant sole for a better protection against perforation or falling of heavy objects.

It has a fuel and oil resistant contact outsole.

### SECTORS

Light Industries

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

## TECHNICAL FEATURES

Color	Black	Main assembly	Injected
Weight	624 gr	Closing	Scratch closure
Upper	Full grain leather	Lining	Breathable 3D mesh
Toecap	Steel		
Puncture resistant sole	Steel		
Midsole	PU		
Outsole	PU		
Insole	Removable, perforated EVA		

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/08/23/1304

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2022

S1P

Safety shoes

**S1P** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance